

PRODUCT DATA SHEET – AVISTA Green Kernsolvat KS 100

Date: 22-10-2021

Parameter	Unit	Test Method	Typical Values
Colour		ISO 2049	0,5 - 1.0
Density 15°C	kg/m ³	ISO 12185	840 - 855
Viscosity 40°C	mm ² /s	ISO 3104	22,0 – 26,0
Viscosity 100°C	mm ² /s	ISO 3104	4,4 – 4,9
Viscosity Index		ISO 2909	>115
Acid Number	mg KOH/g	ASTM D 974	≤ 0.03
Flashpoint COC	°C	ISO 2592	≥ 210
Pour Point	°C	ISO 3016	≤ -9
Noack Evaporation Loss	wt.%	DIN 51 581	<16
Sulfur	wt.%	XRF	≤ 0.2
Copper Corrosion	3h/100°C	EN ISO 2160	1
C _A	%	DIN 51 378-K	2

AVISTA Green

Juelsmindevej 6/18 ♦ DK-4400 Kalundborg ♦ Telefon +45 5956 5644 ♦ CVR 3965 6795 ♦ <http://avistagreen.dk> ♦ avista@avista-oil.dk
 Handelsbanken: Reg.nr.: 6500 ♦ Kontonr.: 0002032244 ♦ IBAN DK3765000002032244 ♦ SWIFT: HANDDKKK